

# AQUARIA 16 / 16T

AQUARIA 16 Code 01440

AQUARIA 16T Code 01446



Design by Ercoli & Garlandini

## FEATURES

Dehumidification capacity: 16l/24h  
Tank capacity: 2 l  
Electrical Resistance 1000W (only version 16T)  
Sound power: only 40 dB (A)  
Digital control  
Drying mode: constant and fast dehumidification  
LCD Display  
Full tank alarm  
Constant condensation disposal  
Electronic defrosting device  
Visible water level and transparent tank  
Handle  
For rooms up to: 75 m<sup>3</sup>



### PURE SYSTEM

Mechanic air filtration system, for better air quality.



### SUPER DEHUMIDIFICATION

Combines dehumidification with heating thanks to a 1000 W electrical element that significantly reduces dehumidification time.



### DIGITAL CONTROL

Multifunction electronic panel, to set the desired humidity level and activate the Drying mode, Equipped with back-lit LCD display to view humidity level and ambient temperature.



### COMPACT TECHNOLOGY

In just 25 cm of depth and a height of 45 cm, a dehumidification capacity of 16 l/24h.



### EASY TO USE

Equipped with barycentric and ergonomic handle, and wheels for easier transport.



### TURBO/DRYING

This function optimizes the laundry's drying process by constantly operating the dehumidifier at full power.



|  |                   | AQUARIA 16           | AQUARIA 16T          |
|--|-------------------|----------------------|----------------------|
|  | Code              | 01440                | 01446                |
|  | EAN               | 8021183014402        | 8021183014464        |
| Dehumidification capacity (2)                              | l/24h             | 16                   | 16                   |
| Heating power  | W                 | -                    | 1000                 |
| Power absorption in dehumidification mode (1)              | W                 | 243                  | 243                  |
| Max. power absorption in dehumidification mode (2)         | W                 | 312                  | 312                  |
| Max. power absorption in dehumidification+heating mode (2) | W                 | -                    | -                    |
| Fan speed  |                   | 1                    | 1                    |
| Tank capacity  | l                 | 2                    | 2                    |
| Air volume ( max )   | m <sup>3</sup> /h | 170                  | 170                  |
| Dimensions ( W x H x D )                                   | mm                | 305 x 464 x 261      | 305 x 464 x 261      |
| Gift box Dimensions ( W x H x D )                          | mm                | 365 x 525 x 300      | 365 x 525 x 300      |
| Noise level  | db(A)             | 40                   | 40                   |
| Weight   | Kg                | 12                   | 12                   |
| Refrigerant gas / Charge                                   | Type / kg         | R410A / 0,130 / 1430 | R410A / 0,130 / 1430 |
| Power supply   | V-F-Hz            | 230 - 1 - 50         | 230 - 1 - 50         |
| Power supply min - max                                     | V                 | 216/244              | 216/244              |
| Air filter   |                   | √                    | √                    |
| Carbon filter  |                   |                      |                      |
| Fotocathalitic filter                                      |                   |                      |                      |
| HEPA filter  |                   |                      |                      |
| Continuous operation with hose                             |                   | √                    | √                    |
| Mechanical controls  |                   |                      |                      |
| Digital control  |                   | √                    | √                    |
| Mechanical Humidostat                                      |                   |                      |                      |
| Digital Humidostat   |                   | √                    | √                    |
| Display LCD  |                   | √                    | √                    |
| Backlight LED Display                                      |                   |                      |                      |
| Indoor humidity visualizer                                 |                   | √                    | √                    |
| Indoor temperature visualizer                              |                   | √                    | √                    |
| Full tank alarm  |                   | √                    | √                    |
| Defrosting device  |                   | √                    | √                    |
| Mot gas defrosting system                                  |                   | √                    | √                    |
| Dehumidifying + heating function                           |                   |                      | √                    |
| Handle   |                   | √                    | √                    |
| Wheels   |                   |                      |                      |
| Tank with push-pull locking                                |                   |                      |                      |
| Tank with Handle   |                   |                      |                      |
| Visible water level  |                   | √                    | √                    |
| Wall mounting kit  |                   |                      |                      |

(1) DB 27°C - WB 21°C ( 27°C - 60% RH )

(2) DB 32°C - WB 29°C ( 32°C - 80% RH )