

NEW

AQUARIA SILENT 15 P

AQUARIA SILENT 15 P Code 01977



FEATURES

- Dehumidification capacity: 15 lt/24h
- Silent: sound level <36 dB(A)
- Display LED
- Tank capacity: 2 lt
- Humidity and temperature display visualization
- Auto mode: keeps relative humidity at optimal level
- Dry function: continuous dehumidification
- Sleep Function: lowest fan speed and display light off
- Continuous draining mode
- Washable antidust filter
- Active carbon filter
- Rear carrying handle
- Wheels for transportation
- Autoshut off with full tank
- Automatic defrost function
- For rooms up to: 70 m³



SILENT SYSTEM
Less than 36 dB(A) sound level.




DIGITAL CONTROL PANEL
LED display and digital controls.




LAUNDRY MODE
For quick drying of laundry.



PRACTICAL
Thanks to the handle and the transportable wheels.



HUMIDITY CONTROL
Manual or automatic customisable comfort.



PURE SYSTEM
Anti-dust filter and active carbon filter, for better air quality.

AQUARIA SILENT 15 P

	Code	01977
	EAN	8021183019773
Dehumidification capacity (2)	l/24h	15
Heating power	W	-
Power absorption in dehumidification mode (1)	W	156
Nominal absorption in dehumidification mode (1)	A	0.88
Max. power absorption in dehumidification mode (2)	W	180
Max. absorption in dehumidification mode (2)	A	0,95
Max. power absorption in dehumidification mode (U.L.U.)	W	210
Protection level		IP 20
Fan speed		2
Tank capacity	l	2,0
Air volume (max)	m ³ /h	110
Dimensions (Larg. x Alt. x Prof. con ruote)	mm	280 x 500 x 200
Gift box Dimensions (W x H x D)	mm	344 x 555 x 264
Noise level	dB(A)	≤36
Weight (without packaging)	kg	12
Weight (with packaging)	kg	13.5
Refrigerant gas	Type	R290
Global warming potential of refrigerant GWP	kg CO ₂ eq.	3
Global warming potential of refrigerant	Tonn. CO ₂ eq.	-
Refrigerant gas charge	kg	0.06
Minimum floor area for installation, use and storage	m ²	4,00
Power cable (N° pole x section mmq)	mm ²	3 x 0.75
Plug		Schuko
Power supply	V-F-Hz	220-240 - 1 - 50
Power supply min - max	V	207- 254
Conformity Mark		CE
Protection level Mark		TUV SUD-GS
Air filter		✓
Carbon filter		✓
Continuous operation with hose		✓
Constant condensation disposal		✓
Indoor humidity visualizer		✓
Indoor temperature visualizer		✓
Full tank alarm		✓
Timer (turn on and turn off)		✓
Sleep function		✓
child lock		✓
Laundry function		✓
Defrosting device		✓

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)